

<sup>12</sup>  
an engaging portion formed near a peripheral wall portion of said shaft  
supporting portion;  
<sup>6</sup>  
a second bracket holding said first bracket;  
<sup>12</sup>  
an engagement portion adapted so that the engaging portion is slidably inserted  
into the engagement portion; and  
<sup>31</sup>  
fixing means fixing said first bracket and said second bracket to said panel.

2. (Amended) A bracket for mounting an auxiliary machinery to a vehicle  
body according to claim 1, further comprising:

an opening portion which is formed in said second bracket and to which said  
shaft supporting portion is inserted; and

a guide holding plate forming the engagement portion, in a peripheral edge  
portion of said opening portion.

4. (Amended) A bracket for mounting an auxiliary machinery to a vehicle  
body according to claim 3, wherein said engaging portion includes a guide portion  
protruding to a side portion of said shaft supporting portion, and said engagement  
portion is a guide groove formed in said guide holding plate.

5. (Amended) A bracket for mounting an auxiliary machinery to a vehicle  
body according to claim 4, wherein said engaging portion also includes a step portion  
formed below said guide portion and engaging with said locking projection.

FINNEGAN  
HENDERSON  
FARABOW  
GARRETT &  
DUNNER LLP

1300 I Street, NW  
Washington, DC 20005  
202.408.4000  
Fax 202.408.4400  
www.finnegan.com

10. (Amended) A bracket for mounting an auxiliary machinery to a vehicle body according to claim 1, further comprising a spacer piece formed in one of said first bracket and said second bracket and brought into contact the other of said first and second brackets so as to keep a predetermined distance with respect to said other of said first and second brackets.

11. (New) A vehicle body mounting bracket for fixing an auxiliary machinery to a panel in a vehicle body side, comprising:

- a first bracket arranging and supporting said auxiliary machinery to one side;
- a shaft supporting portion protruded from said first bracket and fitting a fixed shaft supporting said auxiliary machinery to another side;
- an engaging portion formed near a peripheral wall portion of said shaft supporting portion;
- a second bracket holding said first bracket;
- an engagement portion which is formed on said second bracket and with which said engaging portion is engaged by assembling said first bracket; and
- fixing means fixing said first bracket and said second bracket to said panel;
- an opening portion which is formed in said second bracket and to which said shaft supporting portion is inserted;
- a guide holding plate forming the engagement portion to which said engaging portion is slidably inserted, in a peripheral edge portion of said opening portion; and

FINNEGAN  
HENDERSON  
FARABOW  
GARRETT &  
DUNNER LLP

1300 I Street, NW  
Washington, DC 20005  
202.408.4000  
Fax 202.408.4400  
www.finnegan.com

a locking projection locked in a state that said engaging portion is engaged with said engagement portion and formed in said engaging portion or said engagement portion,

wherein said engaging portion includes a guide portion protruding to a side portion of said shaft supporting portion, and said engagement portion is a guide groove formed in said guide holding plate.

12. (New) A bracket for mounting an auxiliary machinery to a vehicle body according to claim 11, wherein said engaging portion also includes a step portion formed below said guide portion and engaging with said locking projection.

13. (New) A vehicle body mounting bracket for fixing an auxiliary machinery to a panel in a vehicle body side, comprising:

a first bracket arranging and supporting said auxiliary machinery to one side;

a shaft supporting portion protruded from said first bracket and fitting a fixed shaft supporting said auxiliary machinery to another side;

an engaging portion formed near a peripheral wall portion of said shaft supporting portion;

a second bracket holding said first bracket;

an engagement portion which is formed on said second bracket and with which said engaging portion is engaged by assembling said first bracket; and

fixing means fixing said first bracket and said second bracket to said panel; and

FINNEGAN  
HENDERSON  
FARABOW  
GARRETT &  
DUNNER LLP

1300 I Street, NW  
Washington, DC 20005  
202.408.4000  
Fax 202.408.4400  
www.finnegan.com

connectors arranged in said first bracket and said second bracket and connected to each other in a paired manner in a state of assembling the first and second brackets, wherein a wire connected to an electrical equipment of the auxiliary machinery is connected to said connector arranged in said first bracket, and a wire in a side of the vehicle body is connected to said connector arranged in said second bracket.

14. (New) A vehicle body mounting bracket for fixing an auxiliary machinery to a panel in a vehicle body side, comprising:

- a first bracket arranging and supporting said auxiliary machinery to one side;
- a shaft supporting portion protruded from said first bracket and fitting a fixed shaft supporting said auxiliary machinery to another side;
- an engaging portion formed near a peripheral wall portion of said shaft supporting portion;
- a second bracket holding said first bracket;
- an engagement portion which is formed on said second bracket and with which said engaging portion is engaged by assembling said first bracket; and
- fixing means fixing said first bracket and said second bracket to said panel; and
- a spacer piece formed in one of said first bracket and said second bracket and brought into contact the other of said first and second brackets so as to keep a predetermined distance with respect to said other of said first and second brackets.

**IN THE DRAWINGS:**

With this Amendment, Applicants submit a Request for Approval of Drawing Change with marked copies of FIGs. 1-4 adding a legend designating the figures as prior art.

FINNEGAN  
HENDERSON  
FARABOW  
GARRETT &  
DUNNER LLP

1300 I Street, NW  
Washington, DC 20005  
202.408.4000  
Fax 202.408.4400  
[www.finnegan.com](http://www.finnegan.com)